

IN THE CLAIMS

Kindly amend claims 1, 6 and 11 as follows.

The following is a complete listing of revised claims with a status identifier in parenthesis.

LISTING OF CLAIMS

1. (Currently Amended) A connection device comprising:

one or more processing units; and

an optical switch ~~adapted to connect at least one of the units to one or more non-amplified~~ for receiving non-processed optical signals and for connecting at least one of the units to one or more of the received signals based on a characteristic of each signal.
2. (Original) The device as in claim 1 wherein the at least one unit comprises a Raman pump.
3. (Original) The device as in claim 1 wherein the at least one unit comprises an optical-to-electrical-to-optical regenerator.
4. (Original) The device as in claim 1 wherein the at least one unit comprises a dispersion equalization/compensation unit.
5. (Original) The device as in claim 1 where the at least one unit comprises a performance monitor.
6. (Currently Amended) A router comprising:

one or more processing units; and

an optical switch ~~adapted to connect at least one of the units to one or more non-amplified~~ for receiving non-processed optical signals and for

connecting at least one of the units to one or more of the received signals based on a characteristic of each signal.

7. (Original) The router as in claim 6 wherein the at least one unit comprises a Raman pump.

8. (Original) The router as in claim 6 wherein the at least one unit comprises an optical-to-electrical-to-optical regenerator.

9. (Original) The router as in claim 6 wherein the at least one unit comprises a dispersion equalization/compensation unit.

10. (Original) The router as in claim 6 wherein the at least one unit comprises a performance monitor.

11. (Currently Amended) A method for providing an optical, service-enabled connection comprising:

receiving non-processed optical signals; and

connecting at least one of a number of processing units to one or more ~~non-amplified~~ of the received optical signals based on a characteristic of each signal.

12. (Original) The method as in claim 11 wherein the at least one unit comprises a Raman pump.

13. (Original) The method as in claim 11 wherein the at least one unit comprises an optical-to-electrical-to-optical regenerator.

14. (Original) The method as in claim 11 wherein the at least one unit comprises a dispersion equalization/compensation unit.

15. (Original) The method as in claim 11 wherein the at least one unit comprises a performance monitor.